

# CompactCom™ M40 for BACnet/IP

The Anybus CompactCom M40 for BACnet/IP is a complete communication module which is integrated into an industrial device to make it communicate on a BACnet/IP network. BACnet/IP is commonly used in buildings and facility management systems.

By implementing the CompactCom concept into your product line, you will have instant access to any other industrial network by simply plugging in another Anybus module.



## Why worry about networking?

*Once you have implemented the Anybus CompactCom concept, you don't have to worry about network upgrades or certifications. HMS takes care of the network maintenance, so you can focus on your products.*

## If you need fast BACnet communication

The Anybus CompactCom M40 enables fast communication between your device and a BACnet/IP network.

The module supports generic device profiles and comes with a dual port switch implemented in the network processor — the award-winning Anybus NP40.

The communication profile is the B-ASC with data sharing support for analog, binary and multi state value objects types. The module also supports Change of Value notifications and Alarm/Event functionality.

In addition, the module supports web functions such as a webserver for creating Dynamic Webpages which include reading and writing of ADIs and process data, email sending and FTP for downloading of user webpages.

Through the socket interface the module provides the possibility to implement other TCP/UDP protocols using the modules TCP/IP stack.

## Features and benefits

- A complete, interchangeable communication module with connectors
- Short in-design with free assistance from HMS ensures a fast time to market
- Event-based interface method enables easy access to input and output data at any time
- Fast, event-based application hardware interfaces: 8/16-bit parallel and highspeed SPI. I/O (shift register interface) is also available
- BACnet/IP is one of the networks included in the Anybus CompactCom Common Ethernet concept meaning that you can use the same hardware and download the Ethernet network of choice.
- Solid security: Mandatory software signatures prevent unauthorized software to be downloaded to the module. Furthermore, encryption is used to prevent illicit copying.

## CompactCom 40-series

The M40 is part of the Anybus CompactCom 40-series — communication products in chip, brick and module formats. The 40-series is especially suitable for modern and demanding industrial applications.



## Innovative mounting


The Anybus module plugs into a CompactFlash™ connector which is integrated onto the host PCB. HMS offers a CompactFlash connector specifically tailored for the CompactCom module.




# Technical specifications

Technical Details	
Dimensions (L • W • H)	52•50•22 mm, 2.04•1.97•0.86" 51•37•16 mm, 2.01•4.46•0.63" (modules without housing)
Protection class	IP20
RoHS Compliance	Yes
Galvanically isolated network interface	Yes
Application interfaces	- 8/16-bit parallel (30 ns access) - High speed SPI, baudrate configurable up to 20 MHz - I/O (shift register interface, cyclical update time 82 µs) - UART (for backwards compatibility with 30-series, max 625kbps)
Profile support	B-ASC
Connectors	2x RJ45 100 Mbit/s)
LED indicator	Integrated on front (with housing), via application interface (without housing). Indicates Module Status and Network Status.
Certifications	
CE, CULUS, RoHS	Yes
Network conformance	Yes (Pretested internally)
CE - Declaration of Pre-Conformity	
Emission EN 61000-6-4	EN55016-2-3 Radiated emission EN55022 Conducted emission
Immunity EN 61000-6-2	EN61000-4-2 Electrostatic discharge, EN61000-4-3 Radiated immunity. EN61000-4-4 Fast transients/burst, EN61000-4-5 Surge immunity. EN61000-4-6 Conducted immunity.
Electrical Characteristics	
Power requirements	3.3 VDC, +/- 0.15 VDC
Environmental Characteristics	
Operating temp	-40 to 70 °C, -40-158 °F -40 to 85 °C, -40-176 °F (modules without housing)
Humidity	5-95 % non-condensing

BACnet/IP-specific technical highlights
<b>Full Support for B-ASC (BACnet Application Specific Controller)</b>
<b>Alarm and Event Mechanisms</b>
<b>Data Sharing with updates on data changes</b>
<b>Device Management Support</b>
<b>Achilles Storm Tested</b>



Block diagram



## HMS Industrial Networks – Worldwide

### HMS - Sweden (HQ)

Tel : +46 35 17 29 00 (Halmstad HQ)  
E-mail: sales@hms-networks.com

### HMS - Finland

Tel: +358 404 557 381  
E-mail: sales@hms-networks.com

### HMS - Italy

Tel : +39 039 59662 27  
E-mail: it-sales@hms-networks.com

### HMS - UK

Tel: +44 1926 405599  
E-mail: uk-sales@hms-networks.com

### HMS - China

Tel : +86 010 8532 3183  
E-mail: cn-sales@hms-networks.com

### HMS - Germany

Tel: +49 721 989777-000  
E-mail: ge-sales@hms-networks.com

### HMS - Japan

Tel: +81 45 478 5340  
E-mail: jp-sales@hms-networks.com

### HMS - United States

Tel: +1 312 829 0601  
E-mail: us-sales@hms-networks.com

### HMS - France

Tel: +33 368 368 034 (Mulhouse office)  
E-mail: fr-sales@hms-networks.com

### HMS - India

Tel: +91 83800 66578  
E-mail: in-sales@hms-networks.com

### HMS - Switzerland

Tel: +41 61 511342-0  
E-mail: sales@hms-networks.ch

Anybus® is a registered trademark of HMS Industrial Networks AB, Sweden, USA, Germany and other countries. Other marks and words belong to their respective companies. All other product or service names mentioned in this document are trademarks of their respective companies.

Part No: MMA328 Version 1 06/2017 - © HMS Industrial Networks - All rights reserved - HMS reserves the right to make modifications without prior notice.